

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1.-48. (Cancelled)

49. (Currently Amended) A system for manipulating and thermal cycling a sample well tray, comprising:

~~a thermal cycling device generally defining a horizontal cross-sectional area~~
~~and comprising a only one sample block inside the cross-sectional area for~~
~~receiving the sample well tray, the sample block comprising a plurality of~~
~~openings for receiving sample wells of the sample well tray; and~~
a sample well tray handling apparatus comprising:

a sample well tray holder configured to receive the sample well tray
therein;

a rotational actuator configured to rotate the sample well tray holder about
a rotational axis; and

an extension arm extending from the rotational actuator and being
connected to the sample well tray holder,

wherein the sample well tray handling apparatus is configured to move the
sample well tray from a first location ~~outside the cross-sectional area~~ distal
to the sample block to a second location ~~inside the cross-sectional area~~

proximal to the sample block and then later remove the sample well tray from the second location to the first location.

50. (Currently Amended) The system of claim 49, wherein, at the first location, the sample well tray is accessible by a robot ~~that is not part of the thermal cycling device.~~
51. (Previously Presented) The system of claim 49, further comprising a detection unit configured to provide a real-time detection capability during thermal cycling at the second location, wherein operation of the sample well tray handling apparatus does not interfere with the detection unit.
52. (Cancelled)
53. (Currently Amended) The system of claim 49, wherein the sample well tray handling apparatus further comprises a biasing member configured to urge the sample well tray and sample well tray holder in a direction away from the sample block ~~of the thermal cycling device.~~
54. (Previously Presented) The system of claim 53, wherein the biasing member comprises a spring.
55. (Currently Amended) The system of claim 49, further comprising a robot with a robotic arm configured to transport the sample well tray from a third location

~~outside the cross-sectional area of the thermal cycling device~~ distal to the sample block to the first location.

56. (Previously Presented) The system of claim 55, wherein the robotic arm is rotatable between the third location and the first location with respect to a second rotational axis.
57. (Cancelled)
58. (Previously Presented) The system of claim 49, further comprising a sensor for sensing a rotational position of the sample well tray holder.
59. (Previously Presented) The system of claim 49, wherein the rotational angle between the first position and the second position with respect to the rotational axis is approximately 90 degrees.
60. (Previously Presented) The system of claim 49, further comprising a cover configured to press the sample well tray against the sample block when the sample well tray is moved to the second position.